



SAFETY FILMS

AGI 100 ANTI-GRAFFITI

IN & OUT INSTALLATION



ANTI-GRAFFITI / ACIDS / SCRATCHES

PROTECTION AGAINST URBAN VANDALISM

This film is specially designed to facilitate the removal of graffiti and to protect the glass from deliberate attacks and scratches.

The thickness of the film acts as a barrier between the glass and the vandal. The glass remains intact. The film can be easily changed, restoring the glass to its original appearance. Particularly used in: Shops, buses, subways, trains, first floor rooms



Durability: 12 to 15 years for a vertical application in Central Europe.



Use: for all types of glass.



Maintenance : after 30 days with a usual cleaning solution (non abrasive, without ammonia...). Cleaning products that could scratch are not recommended.



Storage: 2 years from delivery. This film must be stored away from excessive humidity and sunlight, at a temperature below 38°C.

In order to meet high standards, we recommend that you do not mix films from different productions

INFORMATION

SUPPORT :PET
THICKNESS :100 microns
PROTECTOR :Siliconized PET 23 microns
APPLICATION SIDE :Internal & External
T° D'APPLICATION :min + 5°C
FIRE RATING : B-s1,d0
STANDARDS :EUROCLASSES
DURABILITY :10 years internal & 5 years external*

*For glazing not exposed to the sun

DIMENSIONS

By roll :



1,52 x

10 m
30 m

Application
Note



Video of the
installation



Method of application

The surface to be bonded must be free of dust, grease or any other contaminant. Some materials such as polycarbonate can cause bubbling problems. A compatibility test is therefore recommended. Possibility to install on plexiglass and polycarbonate.

Production monitoring and standards

In order to constantly improve our productions, we may have to modify without notice the colors and manufacturing processes. We recommend to our users, before applying our films, to make sure that they are exactly suitable for the intended use and to comply with the standards in force.